

Product certificate K56747/07

Issued 2021-12-15

Replaces K56747/06

Page 1 of 3

Vulcanised rubber products for cold and hot drinking water applications

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Duram Industries A.C. LTD.

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K17504 "Vulcanised rubber products for cold and hot drinking water applications" dated 10-10-2018.

Ron Scheepers
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
NL.Kiwa.info@Kiwa.com
www.kiwa.nl

Company

Duram Industries A.C. LTD.
44930 KIBBUTZ RAMAT
HAKOVESH
Israel
Tel: +972 9 7474458
Fax: + 972 9 7474479
duram@netvision.net.il
www.duram.co.il



Certification process
consists of initial and
regular assessment of:








- quality system
- product

Vulcanised rubber products for cold and hot drinking water applications

PRODUCT SPECIFICATION

The products as specified in the table below fulfil the requirements of BRL-K17504. BRL-K17504 covers the requirements of EN 681-1, "Elastomeric seals - Materials requirements for pipe joint seals used in water and drainage applications - Part 1: Vulcanized rubber".

TECHNICAL SPECIFICATION OF THE PRODUCT

Rubber Compound:		EPDM E701A			
Hardness:	70 IRHD	Field of application ² :	I – WA	Remarks:	
Ozone Class ¹ :	I	Production method:	Injection mold		
	Seal type	Easy Fit Seal		Seal type	O-ring
	Nominal Dimensions	75,7 / 90,8 / 112,2 mm		Nominal Dimensions	15x3, 19,2x3, 24x4, 31x5, 62x7, 108x9 mm
	Cross section	6 mm		Cross section	3 - 9 mm
Rubber Compound:		NBR N65WKZ/1 59 IRHD			
Hardness:	59 IRHD	Field of application ² :	I – WA	Remarks:	
Ozone Class ¹ :	III	Production method:	Injection mold		
	Seal type	Series 97 Fittings Shaped Seals		Seal type	Series 1 Seal Shaped Seals
	Nominal Dimensions	38 / 48,6 / 61,6 mm		Nominal Dimensions	38 / 48,6 / 60,6 mm
	Cross section	6 - 8 mm		Cross section	7 - 9 mm
	Seal type	O-ring		Seal type	Plas-Fit Seal
	Nominal Dimensions	49x7, 62x7 mm		Nominal Dimensions	35 – 75 mm
	Cross section	7 mm		Cross section	6 – 8 mm
Rubber Compound:		NBR N65WKZ70			
Hardness:	70 IRHD	Field of application ² :	I – WA	Remarks:	
Ozone Class ¹ :	III	Production method:	Injection mold		
	Seal type	O-ring			
	Nominal Dimensions	15x3, 19,2x3, 24x4, 31x5, 39x6, 62x7, 74x8, 89x8, 108x9, 122,2x10 mm			
	Cross section	3 - 10 mm			
Rubber rings can be supplied with Emulsil 60 lubrication. The rings together with the lubrication form one product that conforms to BRL-K17504.					
1 Ozone resistance class according to BRL-K17504: I For products with a high risk of attack by ozone, for instance in case of separately supplied products without sufficient packaging or in case of connections with preinstalled rubbers under strain; II For products for which a normal resistance to ozone is required; III For rubbers which are never (partly) exposed to the open air when they are in tension. Transport shall always take place in sealed packages.					
2 Field of application class according to BRL-K17504: I Water supply at temperatures up to 50°C; II Hot water supply at temperatures intermittently up to 110 °C, or water supply up to 110 °C in serviceable piping systems; III Hot water circulation systems based on the classification class 2 in ISO 10508;					
Field of application according to EN 681-1: WA As in BRL-K17504 class I; WB As in BRL-K17504 class II; WE As in BRL-2013 class II, for IIR-copolymer;					

Details of the products are included in the drawing list, which forms a part of the IQC schedule.

Kiwa authenticates this list. A copy of this list can be obtained from the producer.

Vulcanised rubber products for cold and hot drinking water applications

Fitness for contact with drinking water

This product is approved on the basis of the requirements for hygienic aspects set in the "Regeling materialen en chemicaliën drink- en warm tapwatervoorziening" ("Materials and chemicals in the supply of drinking water and warm tap water Regulation" dated 01-07-2017; published in the Government Gazette).


These hygienic aspects are based on two main criteria. The product shall permanently comply with:

- The product recipe approved during the assessment procedure. This recipe is not to be changed without prior approval by Kiwa according to the Kiwa approval procedure for the hygienic aspects;
- Specific product requirements for the hygienic aspects.

The recipe and specific product requirements are laid down in the for confidentiality reasons undisclosed 'appendix hygienic aspects' to this certificate.

MARKING

The following marks and indications must be provided on each product[#] and product packaging in a clear, legible and indelible way:

- the name of manufacturer or the deposited trade mark;
- Kiwa (or Kiwa® word mark) and additionally the Kiwa watermark ;
- the nominal dimension or dimensions;
- the nominal hardness;
- the year of manufacturing and preferably the quarter;
- type of rubber applied by means of the letter codes of the nomenclature according to ISO 1629;
- the application class (I, II or III);
- on products from blends, the letter B ("blend") shall be placed behind the first letter code;
- the ozone resistance class ("Ozone I, II or III"). For rubber rings made from two compounds the compound with the lowest class is valid.

[#] If the dimensions of the products are such that the indications applied to them may impair the product, the products may be marked per package in consultation with the manufacturer, the buyer and Kiwa. Products produced by cutting or die cutting out of sheets may be marked per package.

APPLICATION AND USE

The rubber rings are meant to be used in cold water applications (≤ 25 °C).

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Duram Industries A.C. LTD.

and, if necessary,

- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.